

Wave Access Point



Mechanical

Dimensions	212 x 205 x 187 mm (8.3 x 8.1 x 7.4")
Weight	2.3 kg (5.07 lb)
Enclosure materials	Aluminum alloy, UV stabilized polycarbonate
Pole mount diameter	25 to 76 mm (1 to 3") on pipe outer diameter
Wind loading	98 N at 200 km/h (22 lbf at 125 mph)
Weatherproofing	IPX6

Hardware

Processor	Quad ARM® Cortex®-A53 cores at 1.4GHz
Memory	DDR3L 512MB
Networking interface	(1) 2.5GbE RJ45 port (100/1000/2500)* (1) 10G SFP+ port (1/10) <small>*Active only when SFP+ port is down.</small>
Max. power consumption	24W
Power method	48V DC passive PoE 4-pairs (1, 2+; 3, 6-) (4, 5+; 7, 8-) or 2-pairs (4, 5+; 7, 8-) 24V DC passive PoE 4-pairs (1, 2+; 3, 6-) (4, 5+; 7, 8-)
Power supply	48V DC, 0.65A 2.5GbE PoE adapter (included)
Button	Factory reset
LEDs	Power, Ethernet, GPS
Operating temperature	-40 to 60° C (-40 to 140° F)
Operating humidity	5 to 95% noncondensing
Certifications	FCC, IC, CE

Software

OS	airOS®
Operating mode	PtMP access point
Ubiquiti specific features	Wave technology
Services	UISP, ping watchdog, NTP client, SNMP
Tools	Antenna alignment, discovery utility, ping, trace route, speed test
Network	Bridge mode
Software management	Bluetooth management for easy setup over UISP Mobile app WEB UI
Minimum software requirements	Any modern web browser/iOS or Android based smartphone

System

Total throughput	5.4 Gbps (2.7 Gbps duplex)
Supported clients count	15

Range	Connecting to a Wave Long-Range: up to 8 km Connecting to a Wave Nano: up to 5 km
Encryption	WPA2-PSK (AES)

RF

Operating frequency*	57 to 71 GHz <small>*Depends on regulatory region.</small>
GPS	Yes
Channel bandwidth	2160, 1080 MHz
Operating channels*	58320, 59400, 60480, 61560, 62640, 63720, 64800, 65880, 66960, 68040, 69120, 70200 MHz <small>*Depends on regulatory region.</small>
Modulation	16QAM, QPSK
Antenna gain	24 dBi
Polarization	Vertically linear
Beamwidth	Azimuth: 30° Elevation: 3 dB 3°, 6 dB 4°
Electrical downtilt	0°

Back-Up RF

WiFi standard	802.11ax (WiFi 6)		
Operating frequency*			
	US/CA	U-NII-1	5150 - 5250 MHz
		U-NII-2A	5250 - 5350 MHz
		U-NII-2C	5470 - 5725 MHz
		U-NII-3	5725 - 5850 MHz
	Worldwide	5150 - 5875 MHz	
	<small>*Depends on regulatory region.</small>		
Channel bandwidth	20, 40, 80 MHz		
Modulation	BPSK (½), QPSK (½), QPSK (¾), 16QAM (½), 16QAM (¾), 64QAM (2/3), 64QAM (¾), 64QAM (5/6), 256QAM (¾), 256QAM (5/6), 1024QAM (¾), 1024QAM (5/6)		
Antenna gain	12 dBi		
Cross-pol isolation	10 dB		
Electric downtilt	0°		

LEDs

Power	Flashing white: bootup in progress White: not connected to UISP application Blue: connected to UISP application Flashing blue: locate in progress Blue/white: firmware upgrade in progress
Ethernet	Flashing white: Ethernet traffic detected Flashing blue: SFP+ traffic detected
GPS	Blue: receiving at least (4) GPS satellite signal

