

Technical specifications

Classification	Siren with light alarms
Type of siren	Wireless
Installation method	Indoors and outdoors
Compatibility	All Ajax hubs and radio signal range extenders
Type of notification	Acoustic and LED
Alarm volume	From 85 to 113 dB at a distance of 1 m Adjusted in the Ajax app
Alarm duration	From 3 s to 3 min Adjusted in the Ajax app
Indication of arming mode	Yes
Indication of entry/exit delays	Yes With firmware version 3.50 and higher
Chimes	Yes With firmware version 3.73.1.0 and higher
Power supply	Batteries 4 × CR123A, 3 V Up to 5 years of battery life External power supply 12 V $\overline{=}$, 1.5 A
Jeweller communication technology	
Frequency bands	866.0 – 866.5 MHz 868.0 – 868.6 MHz 868.7 – 869.2 MHz 905.0 – 926.5 MHz 915.85 – 926.5 MHz 921.0 – 922.0 MHz (depends on the region of sales)
Maximum effective radiated power (ERP) \leq 20 mW	
Radio signal modulation	GFSK
Communication range	up to 1,500 m in an open space
Polling interval	12–300 s Adjusted by PRO or user with system configuration rights

Operating temperature range	From -25°C to +50°C
Operating humidity	Up to 95%
Protection class	IP54
Anti-sabotage	Protection against forgery Jamming detection Tamper against enclosure opening Accelerometer against detachment
Dimensions	200 × 200 × 51 mm
Weight	528 g
Warranty	24 months from the date of sale
Complete set	StreetSiren SmartBracket mounting panel 4 × CR123A battery (pre-installed) Installation kit Quick Start Guide