

## Technical Specifications

### Mechanical

<b>Dimensions</b>	Without mount: 150 x 64 x 38.4 mm (5.9 x 2.5 x 1.5") With mount: 152.7 x 69 x 47.8 mm (6 x 2.7 x 1.9")
<b>Weight</b>	Without mount: 258.3 g (9.1 oz) With mount: 294 g (10.4 oz)
<b>Enclosure material</b>	Polycarbonate
<b>Mount material</b>	Polycarbonate
<b>Pole mount diameter</b>	>45 mm (1.8") on pipe outer diameter

### Hardware

<b>Networking interface</b>	(1) GbE RJ45 port
<b>Max. camera resolution</b>	Width: 3840 pixels Height: 2160 pixels
<b>Power method</b>	PoE PoE+ input required for PoE output (12.95W) PoE++ input required for PoE+ output (25.5W)
<b>LEDs</b>	Blue/white
<b>Button</b>	Factory-reset
<b>Ambient operating temperature</b>	-20 to 40° C (-4 to 104° F)
<b>Ambient operating humidity</b>	20 to 90% noncondensing
<b>Certifications</b>	FCC, IC, CE

### Software

<b>Web application</b>	UniFi Protect: Version 5.1 and later
<b>Mobile app</b>	UniFi Protect iOS™ and Android™